

FIREGUARD® STEEL TANKS



Fireguard® tanks are fire rated, thermally insulated, lightweight double walled above ground steel tanks (AST).

Tank Solutions Fireguard® tanks are manufactured under license to the Steel Tank Institute and participate in the Fireguard® SwRI 93-01 4-hour rated program.

Fireguard® tanks have passed testing to receive the Underwriters Laboratories UL 2085 listing as a Ballistic Protected and Fire-Resistant AST. The interstitial space monitoring and emergency venting make Fireguard® a safe and convenient solution for above ground storage of flammable and combustible products.

FIREGUARD® SWRI 93-01 FEATURES:

- ✓ 150mm Thick Monolithic Insulation provides SwRI 95-03 approval for four (4) hour fire-rating (240/240/240)
- ✓ Primary storage tank and secondary containment suitable for a wide range of fuels and chemicals, including biodiesel and ethanol
- ✓ Cylindrical, Rectangular and Vertical orientation with both standard and customisation options to suit the application
- ✓ Complies with requirements of AS1940

APPLICATIONS

- ✓ Data Centres
- ✓ High Rise
- ✓ Hospitals
- ✓ Carparks

▶ OPTIONS

Cylindrical, Rectangular or Vertical

▶ CAPACITIES

1,000 - 110,000 litres

▶ COMPARTMENTS

Available Upon Request

▶ DIAMETERS/TYPE

Rectangular, Square & Cylindrical
Subject to style, design and custom requirements

